Table of Contents

| ABST | TRACT | |
|------------------|--|-------------------|
| TABL | LE OF CONTENTS | i |
| LIST | OF FIGURES | ix |
| LIST OF EXAMPLES | | xi |
| LIST | OF TABLES | xiii |
| LIST | OF EQUATIONS | XV |
| | | |
| <u>Cha</u> j | pter 1: Introduction | |
| 1.0 | CHAPTER OVERVIEW | 1-1 |
| 1.1 | THE ENERGY STANDARDS 1.1.1 Legal Requirements | 1-1 1-2 |
| | 1.1.2 Organization of Standards | 1-2 |
| | 1.1.3 California Climate Zones | 1-2 |
| 1.2 | BASIC APPROACHES TO COMPLIANCE | 1-5 |
| 1.3 | HISTORY OF THE STANDARDS | 1-7 |
| 1.4 | CHANGES IN THE 1995 STANDARDS 1.4.1 Structural 1.4.2 Technical | 1-8 1-8 1-8 |
| 1.5 | ORGANIZATION OF THIS MANUAL | 1-10 |
| <u>Cha</u> j | pter 2: Scope and Application | |
| 2.0 | CHAPTER OVERVIEW | 2-1 |
| 2.1 | INTRODUCTION 2.1.1 When Standards Apply | 2-1 2-1 |
| | 2.1.2 Basic Scope and Application Concepts A: Conditioned Space Definitions B: Occupancies | 2-3 2-3 2-6 |

Table of Contents

| 2.2 | 2.2.1 | Unconditioned Space | 2-7 2-7 |
|--------------|--------------|--|--------------------------------------|
| | 2.2.2 | Newly Conditioned Space | 2-7 |
| | 2.2.3 | New Construction in Existing Buildings | 2-9 |
| | 2.2.4 | Alterations to Occupied Spaces | 2-9 |
| | 2.2.5 | Additions | 2-11 |
| | 2.2.6 | New BuildingsA: Speculative, Known OccupancyB: Speculative, Unknown OccupancyC: Mixed UseD: Semi-Conditioned | 2-12 2-12 2-13 2-13 2-14 |
| | 2.2.7 | Change of Occupancy | 2-14 |
| | 2.2.8 | Repair | 2-14 |
| <u>Cha</u> r | oter 3: | Building Envelope | |
| 3.0 | CHAP | TER OVERVIEW | 3-1 |
| 3.1 | INTRODUCTION | | 3-2 |
| | 3.1.1 | Envelope Compliance Approaches | 3-2 |
| | | A: Prescriptive Approach | 3-2 |
| | | B: Performance Approach | 3-2 |
| | 3.1.2 | Basic Envelope Concepts | 3-3 |
| | | A: Definitions | 3-3 |
| | | B: Insulation R-value | 3-7 |
| | | C: Overall Assembly U-value | 3-7 |
| | | D: Wood Frame U-values E: Metal Frame U-values | 3-7 3-9 |
| | | E: Metal Frame U-valuesF: Masonry U-values | 3-10 |
| | | G: Heat Capacity | 3-10 |
| | | H: Fenestration U-values | 3-11 |
| | | I: Solar Heat Gain Coefficient | 3-13 |
| | | J: Relative Solar Heat Gain | 3-13 |
| 3.2 | ENVE | LOPE DESIGN PROCEDURES | 3-15 |
| 3.2 | 3.2.1 | Mandatory Measures | 3-15 |
| | 3.2.1 | A: Doors, Windows and Skylights | 3-15 |
| | | B: Joints and Openings | 3-16 |
| | | C: Insulation Materials | 3-16 |
| | | D: Demising Walls | 3-16 |
| | | <u> </u> | |

ii Nonresidential Manual

| | 3.2.2 | Prescriptive Component Approach A: Exterior Roofs and Ceilings | 3-17 3-17 |
|------|-------------|---|--------------|
| | | B: Exterior Walls | 3-18 |
| | | C: Demising Walls | 3-18 |
| | | D: Exterior Floors and Soffits | 3-19 |
| | | E: Windows | 3-19 |
| | | F: Skylights | 3-21 |
| | | G: Exterior Doors | 3-22 |
| | 3.2.3 | Prescriptive Overall Approach | 3-22 |
| | | A: Overall Heat Loss | 3-24 |
| | | B: Overall Heat Gain | 3-26 |
| | 3.2.4 | Performance Approach | 3-29 |
| | | A: Modeling Envelope Components | 3-29 |
| | 3.2.5 | Alterations | 3-30 |
| 3.3 | ENVE | LOPE PLAN CHECK DOCUMENTS | 3-30 |
| | 3.3.1 | ENV-1: Certificate of Compliance | 3-31 |
| | 3.3.2 | ENV-2: Envelope Component Method | 3-39 |
| | 3.3.3 | ENV-2: Overall Envelope Method | 3-43 |
| | 3.3.4 | ENV-3: Metal Framed Assembly | 3-53 |
| | 3.3.5 | ENV-3: Masonry Wall Assembly | 3-56 |
| | 3.3.6 | ENV-3: Wood Frame Assembly | 3-59 |
| 3.4 | ENVE | LOPE INSPECTION | 3-62 |
| | | | |
| Char | oter 4: | Mechanical Systems | |
| 4.0 | СНАБ | PTER OVERVIEW | 4-1 |
| | _ | | |
| 4.1 | | ODUCTION Mechanical Compliance Approaches | 4-2 4-2 |
| | | | |
| | 4.1.2. | Basic Mechanical Concepts | 4-3 |
| | | A. Definitions of EfficiencyB. Definitions of Spaces and Systems | 4-3 4-4 |
| | | C. Types of Air | 4-5 |
| | | D. Air Deliver System | 4-6 |
| | | E. Attics and Return Plenums | 4-6 |
| | | F. Zone Reheat, Recool and Air Mixing | 4-6 |
| | | G. Economizers | 4-7 |

Table of Contents iii

| | H. Unusual Sources of Contaminants | 4-8 |
|-----|---|------|
| | I. Demand Control Ventilation | 4-8 |
| | J. Intermittently Occupied Spaces | 4-8 |
| 4.2 | MECHANICAL DESIGN PROCEDURES | 4-9 |
| | 4.2.1 Mandatory Measures | 4-9 |
| | A. Equipment Certification | 4-9 |
| | B. Control Equipment Certification | 4-10 |
| | C. Pilot Lights | 4-10 |
| | D. Outdoor Ventilation | 4-10 |
| | E. Natural Ventilation | 4-11 |
| | F. Mechanical Ventilation | 4-12 |
| | G. Ventilation System Operation and Controls | 4-16 |
| | H. Required Controls for Space Conditioning Systems | 4-21 |
| | I. Requirements for Pipe Insulation | 4-26 |
| | J. Requirements for Ducts and Plenums | 4-28 |
| | K. Service Water Systems | 4-29 |
| | L. Pool/Spa Heating Systems | 4-31 |
| | 4.2.2 Prescriptive Approach | 4-31 |
| | A. Sizing/Equipment Selection | 4-31 |
| | B. Load Calculations | 4-32 |
| | C. Fan Power Consumption | 4-34 |
| | D. Space Conditioning Zone Controls | 4-37 |
| | E. VAV Zone Controls | 4-38 |
| | F. Economizers | 4-38 |
| | G. Supply-Air Temperature Reset Control | 4-4(|
| | H. Electric Resistance Heating | 4-41 |
| | I. Service Water Heating | 4-41 |
| | 4.2.3 Performance Approach | 4-41 |
| | A. Compliance with a Computer Method | 4-42 |
| | B. Modeling Mechanical System Components | 4-42 |
| | 4.2.4 Alterations/Additions | 4-42 |
| | 4.2.5 Application to Major Systems Types | 4-42 |
| 4.3 | MECHANICAL PLAN CHECK DOCUMENTS | 4-57 |
| | 4.3.1 MECH-1: Certificate of Compliance | 4-57 |
| | 4.3.2 MECH-2: Mechanical Equipment Summary | 4-69 |
| | 4.3.3 MECH-3: Mechanical Ventilation | 4-75 |
| | 4.3.4 MECH-4: Mechanical Sizing and Fan Power | 4-78 |
| 4.4 | MECHANICAL INSPECTION | 4-82 |

iv Nonresidential Manual

Chapter 5: Lighting Systems

| 5.0 | CHAP | TER OVERVIEW | 5-1 |
|-----|----------------|--|--|
| 5.1 | INTRO | INTRODUCTION | |
| | 5.1.1 | Lighting Compliance Approaches | 5-2 |
| | 5.1.2 | Basic Lighting Concepts and Definitions A. Lighting Trade-Offs B. Definitions C. Occupancy Type D. Lighting Controls | 5-3 5-3 5-4 5-7 5-9 |
| 5.2 | LIGHT | TING DESIGN PROCEDURES | 5-10 |
| | 5.2.1 | Mandatory Measures A. Area Controls B. Bi-Level Switching C. Daylit Areas D. Shut-Off Controls E. Display Lighting F. Exterior Lights G. Tandem Wiring H. Certified Automatic Lighting Control Devices I. Certified Ballasts and Luminaires J. High Rise Residential Living Quarters & Hotel/Motel Guest Rooms | 5-10 5-10 5-11 5-11 5-16 5-18 5-18 5-18 5-18 5-20 |
| | 5.2.2 | Prescriptive Approach A. Complete Building Method B. Area Category Method C. Tailored Method D. Simplification for Tenant Spaces E. Summary | 5-24 5-24 5-25 5-28 5-36 5-36 |
| | 5.2.3 | Performance Approach | 5-40 |
| | 5.2.4 | Actual Lighting Power A. Exempt Lighting B. Actual Lighting Power Calculations C. Automatic Lighting Control Credits | 5-40 5-40 5-41 5-43 |
| | 5.2.5 | Alterations | 5-43 |
| 5.3 | LIGHT 5.3.1 | TING PLAN CHECK DOCUMENTS LTG-1: Certificate of Compliance A. LTG-1 Part 1 of 2 B. LTG-1 Part 2 of 2 C. Sample Form: LTG-1 | 5-46 5-46 5-46 5-51 5-52 |

Table of Contents v

| | 5.3.2 | A. Actual Lighting Power B. Allowed Lighting Power C. Sample Form: LTG-2 | 5-54 5-54 5-54 5-56 |
|--------------|----------------|---|---|
| | 5.3.3 | LTG-3: Lighting Controls Credit Worksheet A. Sample Forms: LTG-3 | 5-57 5-58 |
| | 5.3.4 | LTG-4: Tailored LPD Summary and Worksheet A. LTG-4: Part 1 of 3 B. LTG-4: Part 2 of 3 C. LTG-4: Part 3 of 3 D. Sample Form: LTG-4 | 5-59 5-59 5-60 5-61 5-64 |
| | 5.3.5 | LTG-5: Room Cavity Ratio Worksheet (≥ 3.5) A. Rectangular Spaces B. Nonrectangular Spaces C. Sample Form: LTG-5 | 5-67 5-67 5-67 5-68 |
| 5.4 | LIGHT | TING INSPECTION | 5-69 |
| <u>Cha</u> r | oter 6: | Special Topics | |
| 6.0 | CHAP' | TER OVERVIEW | 6.1 |
| 6.1 | PERF0 6.1.1 | DRMANCE APPROACH Summary | 6-2 6-2 |
| | 6.1.2 | Performance Concepts A. Approval of Computer programs B. The Energy Budget C. Compliance With a Computer Method D. Compliance Procedure E. Application Scenarios F. Professional Judgment | 6-2 6-2 6-3 6-4 6-5 6-5 6-8 |
| | 6.1.3 | Analysis Procedures A. Energy Budget B. Source Energy Use | 6-9 6-9 6-10 |
| | 6.1.4 | Performance Plan Check Documents A. PERF-1: Performance Certificate of Compliance B. ENV-1: Envelope Compliance Summary C. ENV-3: Construction Assemblies D. EXISTING-ENV: Performance Method E. MECH-1: Mechanical Compliance Summary F. MECH-2: Mechanical Equipment Summary | 6-11 6-13 6-13 6-14 6-14 6-14 |

vi Nonresidential Manual

| | | G. MECH-3: Mechanical Compliance Summary/ Mechanical VentilationH. LTG-1: Lighting Compliance Summary | 6-14 6-14 |
|-----|----------------|--|------------------------------|
| | 6.1.5 | Performance Inspection | 6-14 |
| 6.2 | HOTE: 6.2.1 | LS AND MOTELS Introduction | 6-15 6-15 |
| | 6.2.2 | Hotel/Motel Compliance Approaches | 6-15 |
| | 6.2.3 | Basic Hotel/Motel Concepts | 6-15 |
| | 6.2.4 | Hotel/Motel Compliance A. Mandatory Measures B. Prescriptive Compliance C. Performance Compliance | 6-15 6-15 6-16 6-17 |
| | 6.2.5 | Hotel/Motel Plan Check Documents | 6-17 |
| | 6.2.6 | Hotel/Motel Inspection | 6-17 |
| 6.3 | HIGH- 6.3.1 | RISE RESIDENTIAL Introduction | 6-17 6-17 |
| | 6.3.2 | High-rise Residential Compliance Approaches | 6-17 |
| | 6.3.3 | Basic High-rise Residential Concepts | 6-18 |
| | 6.3.4 | High-rise Res. Compliance A. Mandatory Measures B. Prescriptive Compliance C. Performance. Compliance | 6-18 6-18 6-18 6-19 |
| | 6.3.5 | High-rise Res. Plan Check Documents | 6-19 |
| | 6.3.6 | High-rise Res. Inspection | 6-19 |
| 6.4 | SAMP | LE FORMS | 6-19 |

APPENDICES

| Appendix A: | Compliance Forms |
|-------------|---|
| Appendix B: | Materials Reference |
| Appendix C: | California Design Location Data |
| Appendix D: | Indoor Air Quality |
| Appendix E: | Certified Computer Programs |
| Appendix F: | Publications Directory |
| Appendix G: | Glossary |
| Appendix H: | Residential Water Heating and Lighting |
| Appendix I: | Plan Check Guides and Inspection Checklists |

Table of Contents vii

viii Nonresidential Manual

LIST OF FIGURES

| Figure 1-1 | Organization of the Nonresidential Standards | 1-3 |
|-------------|--|------------|
| Figure 1-2 | California Climate Zones | 1-4 |
| Figure 1-3 | Nonresidential Standards Flowchart | 1-5 |
| Figure 1-4 | Organization of Chapters 3, 4 and 5 | 1-10 |
| Figure 2-1 | Type of Conditioned Space and Scope of Compliance | 2-8 |
| Figure 3-1 | Requirements for Floor/Soffit Surfaces | 3-4 |
| Figure 3-2 | Requirements for Roof/Ceiling Surfaces | 3-5 |
| Figure 3-3 | Surface Orientations | 3-5 |
| Figure 3-4 | Skylight Area | 3-6 |
| Figure 3-5 | Slope of a Wall or Window (Roof or Skylight slope | |
| | is less than 60°) | 3-6 |
| Figure 3-6 | Overhand Dimensions | 3-13 |
| Figure 3-7 | Graph of Overhang Factors | 3-14 |
| Figure 3-8 | Roof/Ceiling Flowchart | 3-18 |
| Figure 3-9 | Wall Flowchart | 3-18 |
| Figure 3-10 | Floor/Soffit Flowchart | 3-20 |
| Figure 3-11 | Window Flowchart | 3-21 |
| Figure 3-12 | Skylight Flowchart | 3-22 |
| Figure 4-1 | Typical Building Energy Use (Energy Efficiency Report, October 1990, California Energy Commission Publication No. 400-90-003 | 4-2 |
| Figure 4-2 | Integrated Air Economizer | 4-2 4-7 |
| Figure 4-2 | Nonintegrated Air Economizer | 4-7 |
| Figure 4-3 | Water Economizer | 4-7 |
| Figure 4-5 | Pre-Occupancy Purge Flowchart | 4-18 |
| Figure 4-6 | Proportional Control Zone Thermostat | 4-21 |
| Figure 4-7 | Shut-Off and Setback Controls Flowchart | 4-24 |
| Figure 4-8 | Service Water Heating Flowchart | 4-30 |
| Figure 4-9 | Fan Power Consumption Flowchart | 4-34 |
| Figure 4-10 | VAV Fan Performance Curve | 4-36 |
| Figure 4-11 | Economizer Flowchart | 4-39 |
| Figure 4-12 | Supply Air Reset Controls Flowchart | 4-40 |
| Figure 5-1 | Lighting Energy Use (Lighting accounts for 29% of all commercial building electricity use in California) | 5-2 |
| Figure 5-2 | Lighting Compliance Flowchart | 5-3 |
| Figure 5-3 | Bi-Level Switching | 5-12 |
| - | _ | |

Table of Contents ix

| Figure 5-4 | Combined Bi-Level and Daylit Area Switching | 5-13 |
|-------------|--|------|
| Figure 5-5 | Window Daylit Area | 5-14 |
| Figure 5-6 | Skylight Daylit Area | 5-15 |
| Figure 5-7 | Well Index (Efficiency of Well) Graph | 5-15 |
| Figure 5-8 | Timed Manual Override | 5-17 |
| Figure 5-9 | Occupant-sensing Device Shut-off | 5-17 |
| Figure 5-10 | Tandem Wiring | 5-19 |
| Figure 5-11 | Residential and Hotel/Motel Guestroom | |
| | Kitchen Lighting Examples | 5-22 |
| Figure 5-12 | Residential and Hotel/Motel Guestroom | |
| | Bathroom Lighting Examples | 5-23 |
| Figure 5-13 | Complete Building Method Flowchart | 5-25 |
| Figure 5-14 | Area Category Method Flowchart | 5-26 |
| Figure 5-15 | Calculating Lighting Area | 5-26 |
| Figure 5-16 | Chandelier Dimensions | 5-28 |
| Figure 5-17 | Tailored Method Flowchart | 5-29 |
| Figure 5-18 | Throw Distances and Mounting Heights | 5-33 |
| Figure 5-19 | Calculating the Task Area | 5-34 |
| Figure 5-20 | Gross Sales Wall Area | 5-35 |
| Figure 5-21 | RCR for Stack Lighting (see Example 5-14) | 5-36 |
| Figure 5-22 | Lighting Power Density Calculation Flowchart | 5-37 |
| Figure 6-1 | Annual Sources Energy Use Summary | 6-4 |

x Nonresidential Manual

LIST OF EXAMPLES

| Example 2-1 | Research Greenhouse | 2-2 |
|--------------|--|------|
| Example 2-2 | Direct Heating | 2-4 |
| Example 2-3 | Direct Heating | 2-4 |
| Example 2-4 | Direct Cooling | 2-4 |
| Example 2-6 | High-Rise Residential | 2-6 |
| Example 2-7 | New Window | 2-10 |
| Example 2-8 | New Lighting Fixture | 2-10 |
| Example 2-9 | New Interior Partitions | 2-11 |
| Example 2-10 | Altered Duct Work | 2-11 |
| Example 2-11 | Chiller Replacement | 2-11 |
| Example 2-12 | Adding a Mezzanine | 2-11 |
| Example 2-13 | Energy Inefficient Addition | 2-12 |
| Example 2-14 | Minor Occupancy | 2-13 |
| Example 3-1 | RSHG Calculation | 3-15 |
| Example 3-2 | Area Calculation | 3-24 |
| Example 3-3 | Glazing Area Adjustments | 3-25 |
| Example 3-4 | RSHG Determination | 3-27 |
| Example 3-5 | Determining Weighting Factors | 3-28 |
| Example 3-6 | Sample Notes Block – Envelope Mandatory Measures | 3-34 |
| Example 4-1 | Efficiency Compliance | 4-10 |
| Example 4-2 | Efficiency Compliance | 4-10 |
| Example 4-3 | Natural Ventilation | 4-11 |
| Example 4-4 | Ventilation for a Two-room Building | 4-15 |
| Example 4-5 | Minimum VAV CFM | 4-17 |
| Example 4-6 | Purge Period | 4-18 |
| Example 4-7 | Purge with Natural Ventilation | 4-18 |
| Example 4-8 | Purge with Occupancy Timer | 4-18 |
| Example 4-9 | Maintenance of Ventilation System | 4-20 |
| Example 4-10 | Direct Digital Control of Space Temperature | 4-21 |
| Example 4-11 | Perimeter Systems Thermostats | 4-22 |
| Example 4-12 | Office Occupancy Sensor | 4-23 |
| Example 4-13 | Automatic Time Switches with Multiple Systems | 4-23 |
| Example 4-14 | Thermostat with Sensors | 4-23 |
| Example 4-15 | Time Control for Fan Coils | 4-24 |
| Example 4-16 | Isolation Zones | 4-25 |
| Example 4-17 | Isolation Zone Purge | 4-25 |
| Example 4-18 | Pipe Insulation Thickness | 4-27 |
| Example 4-19 | Duct Sealing | 4-29 |

Table of Contents xi

| Example 4-20 | Equipment Sizing | 4-32 |
|--------------|---|------|
| Example 4-21 | 25 HP Limit | 4-35 |
| Example 4-22 | Filtration | 4-35 |
| Example 4-23 | VAV Bypass System | 4-36 |
| Example 4-24 | Calculation of Fan Power | 4-37 |
| Example 4-25 | Minimum VAV CFM | 4-38 |
| Example 4-26 | Heat Pump Sizing | 4-41 |
| Example 4-27 | Series Fan-Powered Box | 4-45 |
| Example 4-28 | Parallel Fan-Powered Box | 4-45 |
| Example 4-29 | Dual-Fan Dual-Duct Fan Power | 4-51 |
| Example 4-30 | Sample Notes – Mechanical Mandatory Measures | 4-61 |
| Example 5-1 | Lighting Trade-Offs: General Lighting | 5-3 |
| Example 5-2 | Lighting Trade-Offs: Display Lighting (Parts 1 & 2) | 5-4 |
| Example 5-3 | Shut-off Control Override | 5-11 |
| Example 5-4 | Manual Switches and Automatic Controls | 5-11 |
| Example 5-5 | Effective Aperture Matrix | 5-14 |
| Example 5-6 | Skylight/Daylit Area | 5-14 |
| Example 5-7 | Skylight Effective Aperture | 5-15 |
| Example 5-8 | Complete Building Method | 5-25 |
| Example 5-9 | Area Category Method | 5-27 |
| Example 5-10 | Chandelier Wattage Allowance | 5-28 |
| Example 5-11 | Office Task Duration | 5-30 |
| Example 5-12 | RCR Calculation | 5-31 |
| Example 5-13 | Private Office | 5-33 |
| Example 5-14 | Stack Lighting RCR | 5-35 |
| Example 5-15 | Simplified Lighting Flowchart, New Building | 5-38 |
| Example 5-16 | Simplified Lighting Flowchart, Alteration | 5-38 |
| Example 5-17 | Simplified Lighting Flowchart, Retail/Grocery Combination | 5-39 |
| Example 5-18 | Track Lighting Power | 5-42 |
| Example 5-19 | Medium Base Fixture Lighting Power | 5-42 |
| Example 5-20 | Sample Notes: Lighting Mandatory Measures | 5-49 |
| Example 6-1 | Performance Trade-offs | 6-4 |

xii Nonresidential Manual

LIST OF TABLES

| Table 1-1 | History of Standards and Manuals | 1-7 |
|------------|---|------|
| Table 3-1 | Standard Air Film R-values | |
| Table 3-2 | Wood Framed Assembly U-values (excerpt from | |
| | Table B-2, Appendix B) | 3-8 |
| Table 3-3 | Wood Framing Percentage | 3-9 |
| Table 3-4 | Metal Framed Assembly U-values (excerpt from | |
| | Table B-2) | 3-9 |
| Table 3-5 | Metal Framing Factors | 3-10 |
| Table 3-6 | Properties of Hollow Unit Masonry Walls | |
| | (excerpt from Table B-4) | 3-10 |
| Table 3-7 | Properties of Solid Unit Masonry and Solid Concrete | |
| | Walls (excerpt from Table B-5) | 3-11 |
| Table 3-8 | Effective R-Values for Interior Insulation Layers | |
| | on Structural Mass Walls (excerpt from Table B-6) | 3-11 |
| Table 3-9 | Thermal Mass Properties | 3-11 |
| Table 3-10 | Default Fenestration Product U-Values | 3-12 |
| Table 3-11 | Default Solar Heat Gain Coefficient | 3-13 |
| Table 3-12 | Overhang Factors | 3-14 |
| Table 3-13 | Maximum Air Infiltration Rates | 3-15 |
| Table 3-14 | Certified Insulating Materials | 3-16 |
| Table 3-15 | Roof/Ceiling Requirements | 3-18 |
| Table 3-16 | Wall Requirements | |
| Table 3-17 | Floor/Soffit Requirements | |
| Table 3-18 | Window Requirements | |
| Table 3-19 | Skylight Requirements | |
| Table 3-20 | Nonresidential Requirements | |
| Table 3-21 | High-Rise Residential and Hotel/Motel Guest | |
| | Room Requirements | 3-23 |
| Table 3-22 | Temperature and Solar Factors | 3-27 |
| Table 3-23 | Glazing Orientation Weighting Factors | 3-28 |
| Table 4-1a | Minimum Ventilation Rates | 4-12 |
| Table 4-1b | UBC Occupant Densities (sf/person) | 4-13 |
| Table 4-2 | Required Minimum Ventilation Rate Per Occupancy | 4-14 |
| Table 4-3 | Pipe Insulation Thickness | 4-27 |
| Table 4-4 | Duct Insulation Requirements | 4-29 |

Table of Contents xiii

| Table 5-1 | Effective Aperture Matrix | 5-13 |
|------------|--|------|
| Table 5-2 | Typical Efficacy of Luminaires | 5-21 |
| Table 5-3 | Complete Building Method Lighting Power Density Values | 5-24 |
| Table 5-4 | Area Category Method LPD Values | 5-26 |
| Table 5-5 | Illuminance Categories for Tasks | 5-29 |
| Table 5-6 | Typical RCRs for Flush/Recessed Luminaires | |
| | (Task height 2.5 ft above floor) | 5-31 |
| Table 5-7 | Illuminance Categories A-E | 5-32 |
| Table 5-8 | Illuminance Categories F-I | 5-32 |
| Table 5-9 | Mounting Height Adustments | 5-33 |
| Table 5-10 | Power Savings Adjustments for Lighting Controls | 5-44 |

xiv Nonresidential Manual

LIST OF EQUATIONS

| Equation 3-1 | Relative Solar Heat Gain | 3-14 |
|--------------|-----------------------------|------|
| Equation 3-2 | Standard Building Heat Loss | 3-24 |
| Equation 3-3 | Proposed Building Heat Loss | 3-26 |
| Equation 3-4 | Standard Building Heat Gain | 3-26 |
| Equation 3-5 | Proposed Building Heat Gain | 3-28 |
| Equation 3-6 | Energy Use Goal | 3-30 |
| Equation 4-1 | Insulation Thickness | 4-27 |

Table of Contents xv